





POLY BAGGER

The machine may be flexible, but the quality is never.



Infusion 3.1 Ready

Two Infinity models to accommodate your need for speed

Both modular or stand-alone versions available

Colates all standard bag formats

Mechanical tucking

Infinity's poly bagger is built for flexibility, reliability and performance. It excels in flexibility because it is capable of collating all standard bag formats for various products including: bathroom roll, household roll, jumbo roll, hard roll and center pull towels for both retail and industrial products. Our machine can even bag folded products! Its mechanical versatility gives you more options. The bagger has an in-line servo diverter and a servo cassette system for product stacking. It also has a quick-change knife system, and sealing jaw system which makes for easy maintenance. Our poly bagger is a great way to add flexibility to your product mix.

POLY BAGGER TECHNICAL DATA



General Information

Models Available: G10 and G20 Product: Tissue/Towel/Folded Packaging Material: Wicketed Bags

Bag Range Dimensions

Width (Cassette): Min – 101.6mm (4"), Max – 508mm (20")
Width (Upender): Min – 151mm (4"), Max – 508mm (20")
Length: Min – 152mm (6"), Max – 965.2mm (38")
Height: Min – 76mm (3"), Max – 406.4mm (16")
Bag Infeed: 1 - 1.5 mil polyethelyne


Wicket Dimensions

Width: Min - 177.8mm (7"), Max - 914.4mm (36") Length: Min - 304.8mm (12"), Max - 1117.6mm (44")

Machine Speed

G10: 10 bags/min G20: 20 bags/min (Dependent upon packaging config.)

Power / Air Requirements




^{*}Max power requirements are subject to change based on country

Change-over Time

Pack to pack: 30 minutes (average)



Sample Configurations



Corporate Headquarters: 2249 American Blvd De Pere, WI 54115, USA Tel: 920-965-0222 European Office : Via Buozzi 55 40057 Cadriano di Granarolo, Bologna, Italy Tel:+39-051-0560980