



VISION G3

Multi-Pack Wrapper

**FAST,
SMALL-PACK
PRODUCTION.**

**FAST
CHANGE-OVERS.**

Telescoping unwind for faster production.

Top and bottom infeed for better product control.

Cantilever overhead design for faster speeds.

Quick change-overs in less than 30 minutes.

Small footprint with easy access to all areas.

On your marks... get set .. GO!
Our new Vision G3 wrapper is breaking records and setting new industry standards in tissue packaging. We have re-invented our wrapper design with performance-enhancing results. Shorter mechanical movements give the new Vision G3 faster speeds and faster change-overs, saving you time and money on the production floor. Other features like a telescoping unwind that adapts to product size and all-around better access make it no surprise why the Vision G3 gives customers an advantage over the competition. Schedule a virtual product demo today.

Infeed Bath Tissue Dimensions

BT Diameter: Min – 90mm (3.54”), Max – 185mm (7.28”)
Two-lane only Diameter: Max – 250mm (9.84”)
BT Cut Length: Min – 90mm (3.54”), Max – 130mm (5.12”)

Infeed Towel Dimensions

HHT Diameter: Min – 270mm (10.60”), Max – 900mm (35.43”)
(on all four lanes)
Two-lane only Diameter: Max – 250mm (9.84”)
HHT Cut Length: Min – 190mm (7.48”), Max – 280mm (11”)

Poly Reel

Width: Max – 1700mm (66.90”)
Diameter: Max – 700mm (27.60”)
Maximum Sheet Cut-off: Min – 220mm (8.66”), Max – 1000mm (39.37”)
Optional external unwind: 1200mm (47.25”)

Minimum Core diameter: 95mm (3.74”)

Final Package

Height: Min – 190mm (3.54”), Max – 330mm (12.00”)
(Optional height - 3 level) Max - 380mm (14.96”)
Length: Min – 180mm (3.09”), Max – 620mm (24.40”)
(Optional length: Min - 95mm (3.75”)
Width: Min – 100mm (3.93”), Max – 600mm (23.60”)

Acceptable Production Variation

Diameter (+/-): Max – 3mm (.12”)
Cut Length (+/-): Max – 2mm (.08”)

Notes

- Single BRT Minimum diameter is 100 mm
- Please consult Infinity if case range requirements are outside of this spec for assessment
- Size change parts may be required to meet full range of machine
- Single BRT, one roll deep pack the minimum length is 100 mm



Sample Configurations

